

DINITROL 582 Contaminate Cleaner

Characteristics:

DINITROL 582 is a transparent and fast-drying cleaning agent for heavily soiled surfaces and where conventional cleaning agents are not sufficient to remove tough contaminations and/or residues. DINITROL 582 is an ideal cleaning agent for the removal of dirty surfaces on glasses, ceramic layers, paints, metals but also for plastics. Nevertheless, the compatibility should be tested before use on plastics and other critical surfaces.

Application:

The cleaning process with DINITROL 582 should be done properly with a suitable lint-free cloth or paperliner. If necessary this process must be repeated. Before further processing, for example with DINITROL 538 plus or DINITROL Activator plus, the cleaned surfaces must be well vented. This product is suitable for professional experienced users only. To ensure the adhesion and material compatibility outside of the windshield replacements of vehicles, preliminary tests must be done.

Further informations are available on request: *Safety Data Sheet*

Safety / Storage:

Storage tightly closed between 0 und 35°C. Use only in well ventilated areas.
 Storage stability: 12 month

Technical datas:

Base:	Benzene
Colour:	clear / transparent
Density:	0.72 g/ml
Flash point:	< -4°C
Boiling range:	95 – 100°C
Container sizes:	1 & 5 L Sachet for one-time-use

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
 Pyrmonter Str. 76
 D-32676 Lügde
 Telefon:
 +49 (0) 52 81 / 9 82 98-0
 Telefax:
 +49 (0) 52 81 / 9 82 98-60
 E-Mail:
 service@dinol.com