

Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PENETRANT LT

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Anticorrosion additive

 \cdot 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: DINOL GmbH Pyrmonter Str. 76 D-32676 Lügde Tel: +49 5281 9829 80 Fax: +49 5281 9829 860 E-mail: msds@dinol.com

• Further information obtainable from: Research & Development

· 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Sensitising

R43: May cause sensitisation by skin contact.

R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws. The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

- Code letter and hazard designation of product: Xi Irritant
- *Hazard-determining components of labelling:* Calcium Sulfonate

· Risk phrases:

10 Flammable.

- 43 May cause sensitisation by skin contact.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

23 Do not breathe vapour/spray.

24 Avoid contact with skin.

37 Wear suitable gloves.

(Contd. on page 2)



Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

(Contd. of page 1)

Trade name: PENETRANT LT

- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

 \cdot 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

· Results of PBT and vPvB assessment

· PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

· Description: Mixture of substances listed below with additions.

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-<50%
EC number: 919-857-5	🗙 Xn R65	
Reg.nr.: 01-2119463258-33	R10-66-67	
-	� Flam. Liq. 3, H226; � Asp. Tox. 1, H304; ॒ STOT SE 3, H336	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	1-<5%
EINECS: 265-150-3	🗙 Xn R65	
	<u>R1</u> 0-66-67	
	� Flam. Liq. 3, H226; � Asp. Tox. 1, H304; � STOT SE 3, H336	
CAS: 61789-86-4	Calcium Sulfonate	1-<5%
	🗙 Xi R43	
	😯 Skin Sens. 1, H317	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water

Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

 $(Contd. \ on \ page \ 3)$

GB



Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Use only in well ventilated areas.

- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·	DNE	ELs
---	-----	-----

64742-48-2	64742-48-9 Naphtha (petroleum), hydrotreated heavy	
Oral	Acute - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Acute - systemic effects, general population	125 mg/kg (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, general population	900 mg/m3 (General Population)
	Long-term - systemic effects, worker	871 mg/m3 (Worker)
A ditte and informations. The list working the method was a discussion of the heads		

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

 \cdot General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

(Contd. on page 4)

(Contd. of page 2)

GB




Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT





Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT

		(Contd. of page 4)
· Vapour pressure At 20 °C:	3 hPa	
· Density At 20 °C:	0.86 g/cm ³ (DIN 51757)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic At 20 °C:	18 s (DIN 53211/4)	
· Solvent content:		
Organic solvents:	47.8 %	
Solids content:	52.2 % (DIN 53216)	
• 9.2 Other information	No further relevant information available.	
· VOC (EU):	47.85 %	
\cdot VOC (EU):	411.5 g/l	
· VOCV:	47.85 %	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>5000 mg/kg (RABBIT)
Inhalative	LC50/4 h	> 4951 mg/l (RAT)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>3000 mg/kg (RAT)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 6)

GB



Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT

Irritant

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

 08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
 08 01 00 wastes from MFSU and removal of paint and varnish
 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR IMDG, IATA	1139 COATING SOLUTION, special provision 640E COATING SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	111



Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT

	(Contd. of page 6
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· 14.7 Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	For ADR and IMDG: Transport and packing are in accordance with the regulation for limited quantities. These products are therefore classified as no dangerous goods.
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
• Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws. The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous

Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

- Code letter and hazard designation of product: Xi Irritant
- *Hazard-determining components of labelling:* Calcium Sulfonate

· Risk phrases:

- 10 Flammable.
- 43 May cause sensitisation by skin contact.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 23 Do not breathe vapour/spray.
- 24 Avoid contact with skin.
- 37 Wear suitable gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 8)

GB



Printing date 17.07.2014

Version number 9

Revision: 30.06.2014

Trade name: PENETRANT LT

(Contd. of page 7)

· National regulations:

· Technical instructions (air):

ClassShare in %NK47.8

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R43 May cause sensitisation by skin contact.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Research & Development

- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- \cdot * Data compared to the previous version altered.