

Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Dinitrol 3125 HS Spray
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DINOL GmbH Pyrmonter Str. 76 D-32676 Lügde Tel: +49 5281 9829 80

Fax: +49 5281 9829 860 E-mail: msds@dinol.com

- · Further information obtainable from: Research & Development
- · 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Acute Tox. 4	H312	Harmful in contact with skin.
STOT SE 3	Н336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

## · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurised container.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

### · Hazard pictograms





GHS02 GHS07

## · Signal word Danger

### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrotreated light

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H312 Harmful in contact with skin.H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P322 Specific measures (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

#### · 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with additions.

Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5	Naphtha (petroleum), hydrotreated heavy <b>X</b> n R65	10-<25%
Reg.nr.: 01-2119463258-33	R10-66-67	
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
	Propane liquefied	10-<25%
EINECS: 200-827-9	<b>→</b> F+ R12	
	🏇 Flam. Gas 1, H220; Press. Gas C, H280	

(Contd. on page



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

	(C	ontd. of page 2)
CAS: 106-97-8	Butane, pure	10-<25%
EINECS: 203-448-7	<b>♦</b> F+ R12	
	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	5-<10%
EC number: 927-241-2	<b>★</b> Xn R65	
Reg.nr.: 01-2119471843-32		
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336; Aquatic Chronic 3, H412	_
CAS: 25619-56-1	Barium alkylnaphtalenesulfonate	1-<5%
	<b>X</b> Xn R20/22; <b>X</b> Xi R36/38	
	• Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	-

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air or oxygen; call for doctor.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Absorb liquid components with liquid-binding material.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

(Contd. of page 3)

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Use only in well ventilated areas.

## Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

T1:4:41-	1::41	. 414	<b>::</b>	4 41	
· Ingredients with	iimii vaiues	s inai reguire	' monuoring	ai ine	workplace:

### 106-97-8 Butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

## · DNELs

## 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	871 mg/m3 (Worker)

## 64742-49-0 Naphtha (petroleum), hydrotreated light

04742-49-0 Napaina (penoteum), nyaroneutea ugat			
Oral	Long-term - systemic effects, general population	300 mg/kg bw/day (General Population)	
Dermal	Long-term - systemic effects, general population	300 mg/kg bw/day (General population)	
	Long-term - systemic effects, worker	300 mg/kg bw/day (Worker)	
Inhalative	Long-term - systemic effects, general population	900 mg/m3 (General Population)	
	Long-term - systemic effects, worker	1500 mg/m3 (Worker)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 5)



Version number 4 Printing date 20.03.2015 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

(Contd. of page 4)

· Respiratory protection: Short term filter device:



Filter AX

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material:  $\geq 0.12$  mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical ar General Information	nd chemical properties
· Appearance:	
Form:	Aerosol
Colour:	Beige
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. -44°C
· Flash point:	< -20 °C (DIN 53213)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	0.6 Vol %

(Contd. on page 6)



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

		(Contd. of page
Upper:	10.9 Vol %	
Vapour pressure At 20 °C:	8300 hPa	
Density At 20 °C:	0.802 g/cm³ (DIN 51757)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/w	ater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	51.3 %	
Solids content:	46.2 % (DIN 53216)	
9.2 Other information	No further relevant information available.	
· VOC (EU):	51.34 %	
· VOC (EÚ):	411.7 g/l	
· VOCV:	51.34 %	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:

ATE (Acı	ite Toxicity	Estimates)	
Oral	LD50	27237 mg/kg	
Dermal	LD50	1501 mg/kg (RABBIT)	
Inhalative	LC50/4 h	523 mg/l	
64742-48	-9 Naphtha	(petroleum), hydrotreated heavy	
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>5000 mg/kg (RABBIT)	
Inhalative	LC50/4 h	> 4951 mg/l (RAT)	
106-97-8	Butane, pu	re	
Inhalative	LC50/4 h	658 mg/l (rat)	
64742-49	-0 Naphtha	(petroleum), hydrotreated light	
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>5000 mg/kg (RABBIT)	



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

(Contd. of page 6)

## Inhalative LC50/4 h 4951 mg/l (RAT)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information: No further relevant information available.
- · Ingestion: Risk of chemical pneumonia if the product reaches the lungs at vomiting or similar.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

	· European waste catalogue	
	16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
Ī	16 05 00	gases in pressure containers and discarded chemicals
Ī	16 05 04*	gases in pressure containers (including halons) containing dangerous substances

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 8)



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

(Contd. of page 7) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D,S-U· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot ADR$ · Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D· IMDG · Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · UN "Model Regulation": UN1950, AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GH302

· Signal word Danger

(Contd. on page 9)



Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

(Contd. of page 8)

### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

Naphtha (petroleum), hydrotreated light

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H312 Harmful in contact with skin.H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P322 Specific measures (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

### · Technical instructions (air):

Class	Share in %
NK	51.3

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- R10 Flammable.
- R12 Extremely flammable.
- R20/22 Harmful by inhalation and if swallowed.
- R36/38 Irritating to eyes and skin.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65 Harmful: may cause lung damage if swallowed.*
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

### · Department issuing MSDS: Research & Development

- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

(Contd. of page 9)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.03.2015 Version number 4 Revision: 08.01.2015

Trade name: Dinitrol 3125 HS Spray

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas C: Gases under pressure: Compressed gas
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

CD