


Printing date 31.03.2015

#### Version number 9

Revision: 26.02.2015



(Contd. on page 2)

GB



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

	(Contd. of page 1)
• Hazard statements	
H226 Flammable l	iquid and vapour.
H317 May cause a	n allergic skin reaction.
· Precautionary stat	ements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection.
P303+P361+P353	<sup>3</sup> IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· 2.3 Other hazards	

*The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).* 

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with additions.

#### · Dangerous components:

· Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5	Naphtha (petroleum), hydrotreated heavy Xn R65	10-<25%
Reg.nr.: 01-2119463258-33	10-66-67 Flam. Liq. 3, H226; SAsp. Tox. 1, H304; STOT SE 3, H336	
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy Xn R65 R10-66-67 Flam. Liq. 3, H226; I Asp. Tox. 1, H304; I STOT SE 3, H336	1-<5%
CAS: 61789-86-4	Calcium Sulfonate Xi R43 Skin Sens. 1, H317	1-<5%

• Additional information: For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.* 

(Contd. on page 3)

GB

<sup>(</sup>Contd. of page 1)



Printing date 31.03.2015

#### Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

(Contd. of page 2)

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:
- Water
- Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Avoid contact with skin, eyes and clothes.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Use only in well ventilated areas.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

		(Contd. of page 3)			
· DNELs					
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy				
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)			
Dermal	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)			
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)			
Inhalative	Long-term - systemic effects, worker	871 mg/m3 (Worker)			
• Additional information: The lists valid during the making were used as basis.					
· 8.2 Exposure controls · Personal protective equipment:					

- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material:  $\geq 0,12 \text{ mm}$ 

#### · Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· 9.1 Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	Light brown	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	130 °C	

GB



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

	(Contd. of page -
Flash point:	42 °C (DIN 53213)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Vapour pressure At 20 °C:	3 hPa
Density At 20 °C:	1.06 g/cm <sup>3</sup> (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic At 20 °C:	65 s (DIN 53211/4)
Solvent content:	
Organic solvents:	17.3 %
Solids content:	82.7 % (DIN 53216)
9.2 Other information	No further relevant information available.
VOC (EU):	17.33 %
<i>VOC (EU):</i>	183.7 g/l
VOCV:	17.33 %

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- $\cdot \ \textbf{10.6 Hazardous decomposition products:} \ Carbon \ monoxide$

#### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity:

\*

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 37098 mg/l

(Contd. on page 6)

GB -



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

			(Contd. of page
64742-48-	9 Naphtha	(petroleum), hydrotreated heavy	
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>5000 mg/kg (RABBIT)	
Inhalative	LC50/4 h	> 4951 mg/l (RAT)	
64742-48-	9 Naphtha	(petroleum), hydrotreated heavy	
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>3000 mg/kg (RAT)	
Primary ir on the skir on the eye	<b>ı:</b> No irrita	nt effect.	
Sensitisati	on: Sensiti	sation possible through skin contact.	

• Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

No further relevant information available.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

(Contd. on page 7)



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

Trade name: DINITROL 3641A - 80

(Contd. of page 6)

SECTION 14: Transport information	
- 14.1 UN-Number - ADR, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR IMDG, IATA	1139 COATING SOLUTION, special provision 640E COATING SOLUTION
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>
14.7 Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x <b>II of</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1139, COATING SOLUTION, special provision 6401 3, III

## SECTION 15: Regulatory information

\*

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 8)

GB



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

(Contd. of page 7)

Trade name: DINITROL 3641A - 80

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

- Calcium Sulfonate
- · Hazard statements

H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction.

· Precautionary statements

•	• Frecaulionary slate	ements
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P243	Take precautionary measures against static discharge.
	P280	Wear protective gloves/protective clothing/eye protection.
	P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
		with water/shower.
	P403+P235	Store in a well-ventilated place. Keep cool.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	17.3

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

- R10 Flammable.
- *R43* May cause sensitisation by skin contact.
- *R65 Harmful: may cause lung damage if swallowed.*
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Research & Development
- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

GB



Printing date 31.03.2015

Version number 9

Revision: 26.02.2015

## Trade name: DINITROL 3641A - 80

	(Contd. of page 8)
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
DNEL: Derived No-Effect Level (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
Flam. Liq. 3: Flammable liquids, Hazard Category 3	
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1	
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
Asp. Tox. 1: Aspiration hazard, Hazard Category 1	
* Data compared to the previous version altered.	
	GB