

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *Dinitrol Penetrant LT Spray*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Anticorrosion additive*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*DINOL GmbH  
Pyrmonter Str. 76  
D-32676 Lügde  
Tel: +49 5281 9829 80  
Fax: +49 5281 9829 860  
E-mail: msds@dinol.com*
- **Further information obtainable from:** *Research & Development*
- **1.4 Emergency telephone number:**  
*Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.*

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02

*Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.*



GHS07

<i>Skin Sens. 1</i>	<i>H317</i>	<i>May cause an allergic skin reaction.</i>
<i>STOT SE 3</i>	<i>H336</i>	<i>May cause drowsiness or dizziness.</i>
<i>Asp. Tox. 1</i>	<i>H304</i>	<i>May be fatal if swallowed and enters airways.</i>

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



*Xi; Sensitising*

*R43: May cause sensitisation by skin contact.*



*F+; Extremely flammable*

*R12: Extremely flammable.*

*R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.*

- **Information concerning particular hazards for human and environment:**

*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*

*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.*

*Warning! Pressurised container.*

*Has a narcotising effect.*

- **Classification system:**

*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

*The product is classified and labelled according to the CLP regulation.*

(Contd. on page 2)

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word Danger****· Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated heavy

Calcium Sulfonate

Naphtha (petroleum), hydrotreated heavy

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

**· Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards**

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (&lt;0,1% benzene alt&lt;3% (w/w) DMSO extract (IP 346)).

**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures****· Description:** Mixture of substances listed below with additions.**· Dangerous components:**

CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Xn R65 R10-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9	Propane liquefied F+ R12 Flam. Gas 1, H220; Press. Gas C, H280	10-<25%

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31









Printing date 27.03.2015

Version number 11

Revision: 27.03.2015

Trade name: Dinitrol Penetrant LT Spray

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7	Butane, pure  F+ R12  Flam. Gas 1, H220; Press. Gas C, H280	10-<25%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy  Xn R65 R10-66-67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  STOT SE 3, H336	1-<5%
CAS: 61789-86-4	Calcium Sulfonate  Xi R43  Skin Sens. 1, H317	1-<5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · After inhalation:

Supply fresh air or oxygen; call for doctor.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing: Do not induce vomiting; call for medical help immediately.

### · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

#### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · For safety reasons unsuitable extinguishing agents: Water with full jet

### · 5.2 Special hazards arising from the substance or mixture No further relevant information available.

### · 5.3 Advice for firefighters

#### · Protective equipment: Mount respiratory protective device.

#### · Additional information Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

### · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 3)

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Use only in well ventilated areas.
- **Information about fire - and explosion protection:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
 Store in a cool location.  
 Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep container tightly sealed.  
 Do not seal receptacle gas tight.  
 Store in cool, dry conditions in well sealed receptacles.  
 Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

#### **106-97-8 Butane, pure**

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
Carc	(if more than 0.1% of buta-1.3-diene)

### · DNELs

#### **64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	871 mg/m <sup>3</sup> (Worker)

- **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · **Personal protective equipment:**

#### · **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.

#### · **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 4)

Short term filter device:



Filter AX

· **Protection of hands:**

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material:  $\geq 0,12$  mm· **Penetration time of glove material**

&gt; 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Light beige
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	-44 °C

· **Flash point:** < -20 °C (DIN 53213)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** > 200 °C· **Decomposition temperature:** Not determined.· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	10.9 Vol %

(Contd. on page 6)

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 5)

· Vapour pressure At 20 °C:	4500 hPa
· Density At 20 °C:	0.818 g/cm <sup>3</sup> (DIN 51757)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	71.8 %
Solids content:	28.2 % (DIN 53216)
· 9.2 Other information	No further relevant information available.
· VOC (EU):	71.79 %
· VOC (EU):	587.3 g/l
· VOCV:	71.79 %

## SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

## SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	3356 mg/l
------------	----------	-----------

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>5000 mg/kg (RABBIT)
Inhalative	LC50/4 h	> 4951 mg/l (RAT)

**106-97-8 Butane, pure**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>3000 mg/kg (RAT)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitisation: Sensitisation possible through skin contact.

(Contd. on page 7)



Printing date 27.03.2015

Version number 11

Revision: 27.03.2015

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 6)

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

No further relevant information available.

· **Ingestion:** Risk of chemical pneumonia if the product reaches the lungs at vomiting or similar.

## SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of as dangerous waste.

· **European waste catalogue**

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

(Contd. on page 8)

GB

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



- |                |             |
|----------------|-------------|
| · <b>Class</b> | 2 5F Gases. |
| · <b>Label</b> | 2.1         |

· **IMDG, IATA**



- |                |     |
|----------------|-----|
| · <b>Class</b> | 2.1 |
| · <b>Label</b> | 2.1 |

· **14.4 Packing group**

- |                          |      |
|--------------------------|------|
| · <b>ADR, IMDG, IATA</b> | Void |
|--------------------------|------|

· **14.5 Environmental hazards:**

- |                            |    |
|----------------------------|----|
| · <b>Marine pollutant:</b> | No |
|----------------------------|----|

· **14.6 Special precautions for user**

- |                                |                 |
|--------------------------------|-----------------|
| · <b>Danger code (Kemler):</b> | Warning: Gases. |
| · <b>EMS Number:</b>           | -               |
|                                | F-D,S-U         |

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

- |                                   |                                    |
|-----------------------------------|------------------------------------|
| · <b>Limited quantities (LQ)</b>  | 1L                                 |
| · <b>Excepted quantities (EQ)</b> | Code: E0                           |
|                                   | Not permitted as Excepted Quantity |
| · <b>Transport category</b>       | 2                                  |
| · <b>Tunnel restriction code</b>  | D                                  |

· **IMDG**

- |                                   |                                    |
|-----------------------------------|------------------------------------|
| · <b>Limited quantities (LQ)</b>  | 1L                                 |
| · <b>Excepted quantities (EQ)</b> | Code: E0                           |
|                                   | Not permitted as Excepted Quantity |

· **UN "Model Regulation":**

UN1950, AEROSOLS, 2.1

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word Danger**

(Contd. on page 9)



**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 8)

· **Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated heavy

Calcium Sulfonate

Naphtha (petroleum), hydrotreated heavy

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	71.8

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R12 Extremely flammable.

R43 May cause sensitisation by skin contact.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development· **Contact:** Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Printing date 27.03.2015

Version number 11

Revision: 27.03.2015

**Trade name: Dinitrol Penetrant LT Spray**

(Contd. of page 9)

*LD50: Lethal dose, 50 percent*

*Flam. Gas 1: Flammable gases, Hazard Category 1*

*Flam. Aerosol 1: Flammable aerosols, Hazard Category 1*

*Press. Gas C: Gases under pressure: Compressed gas*

*Flam. Liq. 3: Flammable liquids, Hazard Category 3*

*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*

*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

GB