

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol

1.3. Details of the supplier of the safety data sheet

Company name: POLYTOP GmbH
Street: Langenselbolder Str. 8
Place: D-63543 Neuberg

Telephone: +49-6183-80014-0 Telefax: +49-6183-80014-14

e-mail (Contact person): info@polytop.de Internet: www.polytop.de

Responsible Department: Zentrale Tel. +49-6183-80014-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (<0,1% benzene)

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of this material and its container to hazardous or special waste collection point.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 2 of 9

Special labelling of certain mixtures

EUH018 In use may form flammable/explosive vapour-air mixture.
EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

see below Labelling for contents according to regulation (EC) No. 648/2004, perfumes (free of allergens 2003/15/EU), Additional information: silicone oil, wax

Hazardous components

| CAS No | Chemical name | | | | | |
|------------|---|--------------|------------------|--|--|--|
| | EC No | Index No | REACH No | | | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | | | |
| 64742-48-9 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (<0,1% benzene) | | | | | |
| | 927-241-2 | | 01-2119471843-32 | | | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066 | | | | | |
| 74-98-6 | propane | | | | | |
| | 200-827-9 | 601-003-00-5 | | | | |
| | Flam. Gas 1; H220 | | | | | |
| 106-97-8 | butane | | | | | |
| | 203-448-7 | 601-004-00-0 | | | | |
| | Flam. Gas 1; H220 | | | | | |

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes.

Further Information

Aerosol propellant. Propan/Butan

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

If victim is at risk of losing consciousness, position and transport on their side.

Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off immediately all contaminated clothing.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Seek medical attention if problems persist.

After ingestion

not applicable

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam.

Extinguishing powder.

Carbon dioxide (CO2).

Sand.

Unsuitable extinguishing media

Water

High power water jet.

Water fog.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air.

In case of fire may be liberated: Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suppress gases/vapours/mists with water spray jet.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Do not rinse down with water.

6.4. Reference to other sections

SECTION 13: Disposal considerations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Handle and open container with care.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition. - No smoking.

Take precautionary measures against static discharges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50° C. Do not pierce or burn, even after use.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 4 of 9

Further information on handling

Do not breathe gas/fumes/vapour/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Advice on storage compatibility

No special precautionary measures are necessary.

Further information on storage conditions

Protect against: moisture.

Do not store at temperatures over: 50°C

Keep container tightly closed.

Keep away from heat.

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|----------|-----------|-----|-------|-----------|---------------|--------|
| 106-97-8 | Butane | 600 | 1450 | | TWA (8 h) | WEL |
| | | 750 | 1810 | | STEL (15 min) | WEL |

8.2. Exposure controls

Protective and hygiene measures

Caution! Container under pressure.

Heating causes rise in pressure with risk of bursting.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn:

Butyl caoutchouc (butyl rubber) >0,7mm

Breakthrough times and swelling properties of the material must be taken into consideration. >240min

Unsuitable material: NR (Natural rubber (Caoutchouc), Natural latex). PVC (Polyvinyl chloride). PVA (Polyvinyl alcohol). CR (polychloroprenes, Chloroprene rubber). Viton

Skin protection

Body protection: not required.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.

Filtering device with filter or ventilator filtering device of type: A/P2



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: not relevant
Odour: product-specific

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:
Initial boiling point and boiling range:
not relevant
Flash point:
not applicable

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 1 vol. % Upper explosion limits: 12 vol. %

Oxidizing properties

not oxidizing.

Vapour pressure: 4000 hPa

(at 20 °C)

Density: not relevant
Water solubility: insoluble
Solvent content: 43%

9.2. Other information

Pressurised container: May burst if heated.

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Caution! Container under pressure.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

not relevant

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 6 of 9

| CAS No | Chemical name | | | | | | |
|------------|---|------|-------------|---------|--------|--|--|
| | Exposure route | Dose | | Species | Source | | |
| 64742-48-9 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (<0,1% benzene) | | | | | | |
| | oral | LD50 | >2000 mg/kg | Rat | | | |
| | dermal | LD50 | >2000 mg/kg | Rabbit | | | |
| | inhalative (4 h) vapour | LC50 | >5 mg/l | Rat | | | |
| | inhalative (4 h) aerosol | LC50 | >5 mg/l | Rat | | | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Practical experience

Other observations

Has de-greasing effect on the skin.

After cleaning apply high-fat content skin care cream.

SECTION 12: Ecological information

12.1. Toxicity

| CAS No | Chemical name | | | | | |
|------------|---|-------|-------------|-----------|---------|--------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source |
| 64742-48-9 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics (<0,1% benzene) | | | | | |
| | Acute fish toxicity | LC50 | 10-100 mg/l | 96 h | | |
| | Acute algae toxicity | ErC50 | >100 mg/l | | | |
| | Acute crustacea toxicity | EC50 | >100 mg/l | 48 h | | |

12.2. Persistence and degradability

Abiotic degradation in Air.

Indication applies to the solvent.

12.3. Bioaccumulative potential

No indication of bio-accumulation potential.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|---------------|---------|
| 74-98-6 | propane | 2,36 |
| 106-97-8 | butane | 2,89 |

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No risks worthy of mention.

Further information

Do not allow to enter into surface water or drains.

Does not enter into waste water by proper application.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 7 of 9

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately

collected fractions (except 15 01); solvents

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Other applicable information (inland waterways transport)

E0



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 8 of 9

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Marine pollutant: no EmS: F-D. S-U

Air transport (ICAO)

14.1. UN number: UN1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A1 A145 A167

Forbidden

Y203

Excepted quantity:

E0

IATA-packing instructions - Passenger: Forbidden IATA-max. quantity - Passenger: Forbidden IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

: Forbidden

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Pressurised container: May burst if heated.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): Volatile organic compounds (VOC) in percentage by weight: 74

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - water contaminating



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Aerosol Dashboard Vinyl Treatment (German: Cockpit-Vinyl-Pflege)

Print date: 12.05.2016 Page 9 of 9

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3.

Relevant H and EUH statements (number and full text)

| H220 | Extremely flammable gas. |
|------|-------------------------------|
| H222 | Extremely flammable aerosol. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May hu |

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH018 In use may form flammable/explosive vapour-air mixture. EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)